



POWER CONSOLES

Electric/Hydraulic

ISO 9001-2000 Registered

For Immediate Assistance in the U.S. Call: 877-777-4046

Outside the U.S. Call: 985-785-3075

Standard Electric Hydraulic Torque Wrench Pump



These pumps have been continually upgraded over the last 40 years and even some of the originals are still in service! Equipped with a 1-1/8 hp, single phase universal motor, they have a noise level of 90-95 dBA. Offer an incredible weight to performance ratio for any of our electric/hydraulic pumps, and are CSA rated for intermittent duty.

- ⚙️ Two-speed High Performance Pump
- ⚙️ External Adjustable Pressure Regulator
- ⚙️ Retract Side Internal Relief Valve
- ⚙️ Use for double or Single Acting Tools
- ⚙️ Hand Remote Control w/30-foot Cord
- ⚙️ Electric Motor
1-1/8 hp, 12,000 rpm
115V, 25 amps
110V/50Hz, 25amps
220V/50Hz, 13 amps

Console Model	Source	Power Req.	Oil Delivery	Oil Reservoir	Usable Oil	Overall width	Overall Length	Overall Height	Weight w/Oil
TL-SEHC	Electric 1-1/8 HP	115V, 110V 220V	704 in ³ @ 100 psi 56 in ³ @ 10,000 psi	2.5 Gallons	525 inches ³	17.14 inches	9.5 inches	18.12 inches	75 pounds

Standard Air/Hydraulic Torque Wrench Pump



- ⚙️ Use where air is the preferred source of power
- ⚙️ External adjustable pressure regulator
- ⚙️ Retract side internal relief valve
- ⚙️ Use for double or single acting tools
- ⚙️ Pneumatic remote control w/30-foot cord
- ⚙️ Powerful 3hp motor starts under load

Console Model	Source	Oil Delivery	Oil Reservoir	Usable Oil	Overall width	Overall Length	Overall Height	Weight w/Oil
TL-SAHC	Pneumatic 3 HP	465 in ³ @ 100psi 55 in ³ @ 10,00psi	2.5 Gallons	590 inches ³	16.55 inches	9.5 inches	19.83 inches	65 pounds

www.torqlite.com



POWER CONSOLES

Air/Hydraulic

ISO 9001-2000 Registered

For Immediate Assistance in the U.S. Call: 877-777-4046

For Assistance Outside the U.S. Call: 713-983-7171

PMU Electric Hydraulic Torque Wrench Pump



Standard heat exchanger package - keeps power console cool under extreme use

Universal motor - for a high power to weight ratio; generates full pressure on as little as 50% of the rated line voltage

Glycerine filled gauge - with scales reading in psi and bar

Adjustable pressure relief valve - for accurate torque adjustments and precise repeatability

Console Model	Source	Power Req.	Oil Delivery	Oil Reservoir	Overall width	Overall Length	Overall Height	Weight w/Oil
PMEEHC 10.5	Electric 1/2 HP	115V, 1ph 50/60Hz	1st Stage - 200in ³ @ 100psi 2nd Stage - 20in ³ @ 10,000psi	.50 Gallons	10 inches	10 inches	14 inches	53 pounds

Custom Air/Hydraulic Torque Wrench Pump



Torq/Lite® manufactures custom built hydraulic consoles for improved tool speed or special applications. These air powered units are a perfect solution when speed of operation is a primary factor. Our custom built, air/hydraulic units deliver constant high volumes at the full range of pressure, 0 to 10,000 p.s.i. This translates into tool speeds 3 to 5 times that achieved with standard hydraulic power consoles.

Console Model #	Maximum Output	Maximum Oil Flow	Reservoir	Weight with Oil	Control
CAHC-3	3,000 psi	7.5 Gals. per minute	9 U.S. Gals	260 lbs.	Push Button; 30' Hose
CAHC-6	6,000 psi	4.0 Gals. per minute	7 U.S. Gals	245 lbs.	Push Button; 30' Hose
CAHC-10	10,000 psi	2.0 Gals. per minute	7 U.S. Gals	245 lbs.	Push Button; 30' Hose

Custom	Source Consoles	Requirements	Width	Length	Height	Gauges
All Models	Pneumatic	90 psi @ 150 cfm	24"	24"	24"	3" Glycerin Filled (Air & Hydraulic)

www.torqlite.com